



S.N. TYPE OPENINGS			SILL	LINTEL
1.	DW1	9'-0"	0'-0"	7'-3"
2.	DW2	6'-6"	0'-0"	7'-3"
3.	DD1	6'-0"	0'-0"	BEAM BOTTOM
4.	DD	5'-0"	0'-0"	
5.	D	4'-0"	0'-0"	7'-3"
6.	D1	3'-6"	0'-0"	7'-3"
7.	D2	3'-4½"	0'-0"	7'-3"
8.	D3	2'-9"	0'-0"	7'-3"
9.	D4	2'-6"	0'-0"	7'-3"
10.	D5	4'-10½"	0'-0"	7'-3"
11.	D6	3'-0"	0'-0"	

1.	W	12'-6"	2'-9"	7'-3"
2.	W1	12'-4"	2'-9"	7'-3"
3.	W2	11'-11"	2'-9"	7'-3"

The diagram illustrates the construction of a door frame and its connection to a flush door. On the left, the wall section shows layers from the outside in: IN SIDE plaster, P.O.P PUNNING 6MM THICK, AVERAGE PLASTER 20MM THICK, another layer of P.O.P PUNNING 6MM THICK, and OUT SIDE plaster. The door frame is made of TEAK WOOD, with a frame size of 75X125 MM. It features an ENAMEL SHADE OFF WHITE finish and a 6MMX6MM GROOVE. The frame is shown in two parts: a vertical section and a horizontal section. Dimensions include a 2 1/2 inch gap between the wall and the frame, a 12MM gap at the top, a 40MM gap at the bottom, a 10MM gap at the side, and a 5 inch gap at the bottom. The door itself is labeled as FLUSH DOOR and 40MM FLUSH DOOR AS PER DESIGN.

NOTES:
THE COPYRIGHT AND PROPERTY OF THIS DESIGN AND DRAWING BELONGS TO **NEERAV GUPTA**. IT MUST NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THEIR WRITTEN CONSENT. A LEGAL ACTION AS PER LAW MAY BE INITIATED AGAINST THE OFFENDER.